



INTERFACE COMPONENTS

- AXTC-LN11 interface
- AXTC-LN11 harness
- 3.5mm adapter

APPLICATIONS

Chevrolet

Cobalt.....2007-2012
 HHR2006-2012
 Malibu2008-2012

Pontiac

G52007-2009
 G62009-2010
 Solstice.....2006-2009

Saturn

Aura2007-2009
 Sky.....2007-2009

Data Interface with SWC

Fits Select GMC Models 2006-2012

INTERFACE FEATURES

- Designed for amplified and non-amplified systems
- Provides accessory power (12-volt 10-amp)
- Retains R.A.P. (Retained Accessory Power)
- Provides NAV outputs (parking brake, reverse, and speed sense)
- Built-in features like SWC & Auto-Detect
- Auto-detect feature - automatically detects the vehicle type, radio connection, and preset controls
- Ability to dual-assign steering wheel control buttons
- Designed to work with major radio brands
- Can be manually programmed for most vehicles
- Retains settings, even after battery disconnection
- Retains chimes
- Retains factory backup camera if equipped
- Retains balance & fade
- Provides 12-volt illumination output
- Micro "B" USB updatable

Product Info



TABLE OF CONTENTS

Connections.....	2
Programming.....	3
Troubleshooting.....	4

TOOLS & INSTALLATION ACCESSORIES REQUIRED


- Crimping tool and connectors, or solder gun, solder, and heat shrink
- Tape
- Wire cutter
- Zip ties

Visit AxxessInterfaces.com for more detailed information about the product and up-to-date vehicle specific applications.




ATTENTION: With the key out of the ignition, disconnect the negative battery terminal before installing this product. Ensure that all installation connections, especially the air bag indicator lights, are plugged in before reconnecting the battery or cycling the ignition to test this product.

NOTE: Refer also to the instructions included with the aftermarket accessory before installing this device.


CONNECTIONS



PROGRAMMING

1.  Open the driver's door, and keep open during the programming process.
2.  Cycle the ignition on.
3.  Connect the **AXTC-LN11 harness** to the **AXTC-LN11 interface**, and then to the wiring harness in the vehicle.
- *4.  Locate the **Volume Up** button on the the steering wheel. Program the interface by holding the **Volume Up** button until the LED stops flashing.
*Only applicable if vehicle came with steering wheel controls
- *5.  The LED will flash **Green & Red** while the interface programs the radio to the steering wheel controls. Once programmed, the LED will go out, then produce a pattern which will identify the radio type installed. Refer to the **Radio LED Feedback** section under **Troubleshooting** for radio types.
*Only applicable if vehicle came with steering wheel controls
6.  The LED will go out, then once again quickly flash **Green & Red** while the interface programs itself to the vehicle. Once programmed, the LED will go out again, then turn solid **Green**.
7.  Cycle the ignition off, then back on.
8.  Test all functions of the installation for proper operation.

TROUBLESHOOTING

- 

If the interface fails to function, press and release the reset button, then repeat the programming process from step 4 to try again.

LED Light Reset Button

QR Code Scan Here



Further troubleshooting steps and information can be located at:

axxessinterfaces.com/product/AXTC-LN11

- #### Final LED Feedback

At the end of programming the LED will turn **Solid Green** which indicates programming was successful. If the LED didn't turn **Solid Green**, reference the list below to understand which programming section the problem may stem from.

LED Light	Radio Programming Section	Vehicle Programming Section
Solid Green	Pass	Pass
Slow Red Flash	Fail	Pass
Slow Green Flash	Pass	Fail
Solid Red	Fail	Fail

Note: If the LED shows **Solid Green** for **Pass** (indicating everything programmed correctly), yet the steering wheel controls don't work, make sure that the 3.5mm jack is plugged in, and plugged into the correct jack in the radio. Once corrected, press the reset button, then program again.

Having difficulties? We're here to help.



Contact our Tech Support line at:

386-257-1187



Or via email at:

techsupport@metra-autosound.com

Tech Support Hours (Eastern Standard Time)

Monday - Friday: 9:00 AM - 7:00 PM

Saturday: 10:00 AM - 5:00 PM

Sunday: 10:00 AM - 4:00 PM



**Metra recommends MECP
certified technicians**